Neutrix

Portable grinding machine for Tungsten electrodes

Replaceable dust filter with dust collector

Triple use of the diamond disc

Minimal waste of electrodes when grinding

 Grinding electrodes as short as 15 mm

> Inelco grinders

The way to grind

NEUTRIX - hand-held Tungsten grinder with an integrated dust filter and dust vcollector

Effective

NEUTRIX is a handheld and portable grinding machine that fulfils the requirements for safe and environmentally friendly grinding of Tungsten electrodes in high quality for TIG and plasma welding. Grinding in the longitudinal direction of the electrode, variable grinding angle, three grinding positions on the diamond disc and the electrode holder ensure efficient grinding.

Mobile and safe

The storage case and low weight make NEUTRIX ideal where there is a need to take the grinder with you. At the same time, the NEUTRIX, is equipped with an integrated dust filter that protects against the harmful grinding dust and collects the dust for safe disposal.

Short electrodes

NEUTRIX can grind electrodes down to lengths of 19 mm and even 15 mm with a special clamp, for example for orbital welding. The inspection cover on the grinder makes it easy to follow the grinding process and to ensure that the electrode is not generating sparks during grinding. This avoids the electrode being damaged by high temperatures.

Simple operation

Insert the electrode in electrode holder and lock it in the stick-out. Set the variable degree scale at the desired angle. Place the electrode holder in the grinder. Start the grinder and rotate the holder until it reaches the stop and the grinding is finished.

Grinder facts

Electrode size: Ø0.8 - 4 mm
Min. length: 19 mm standard (15 mm
with special electrode clamps)
Angles: 15° - 180° tip angle
(7.5° - 90° grinding angle)

Technical specifications

Motor: 110V-50/60 Hz, 220V-50/60Hz

Motor effect: 850 W Weight: 2.8 kg

Speed: 22,000 - 28,000 rpm. Grinding speed: 28 - 50 m/sec.

Standard unit includes

- Complete grinder with diamond disc, filter and storage case
- Electrode holder
- Electrode clamps for Ø1.6, 2.4 and 3.2 mm electrodes (clamps are available for other electrode sizes).

Extra accessories

- Foot for mounting on a work table
- Electrode clamps for all electrodes from Ø0.8 - 4.0 mm
- Electrode clamps for grinding extra short electrodes

Main features of Neutrix

- ·Sealed grinding chamber and dust filter to protect the user
- · Variable angle setting gives more flexibility
- $\bullet\mbox{The 3}$ positions of the diamond disc give optimal utilisation
- Electrode holder ensures centring of the tip and reduces electrode waste
- •Inspection cover so you can follow the grinding process
- ·Powerful motor with speed adjustment



Precise adjustment of the electrode's stick-out.



Adjustable tip angle from 15-180°.



Integrated dust filter, that is easy to change.

