

Purging Tape Products

EZ Zone® Tape

EZ Zone® Tape is a purge gas retaining tape used to seal the root gap between pipes to trap argon gas. Composed of two adhesive sections separated by an adhesive-free center zone. The adhesive portion of the tape never comes in contact with the pipe as it is welded; creating a clean, contaminant-free weld. Halogen and chlorofluorocarbon free.



Part No.	Dimensions	Adhesive Free Zone	Case Qty
EZ-ZT 2.5	2.5" x 75' / 64mm x 23m	1" / 25mm	18
EZ-ZT 4.0	4.0" x 75' / 102mm x 23m	2" / 51mm	12

EZ Tape®

EZ Tape® is a traditional aluminium tape that can be used for sealing the root gap while purging and sealing pipe ends for transport. Conventional uses include; sealing ducts for heating, air conditioning and refrigeration; and acting as a vapour barrier. EZ tape is a high temperature, halogen-free and conforms to irregular surfaces.



Part No.	Dimensions	Case Qty
EZ-T 2.0	2" x 75' / 51 mm x 23 m	24

Fiback®

Fiback® fiberglass backing tape is a heat resistant aluminum tape with a woven fiberglass center strip, designed to eliminate or reduce the need for back purging and post weld grinding. Available in 200 AMP & 600 AMP formats.

Part No.	Dimensions	Case Qty
200 AMP		
AFBT-2.0-200	2.0" x 41' / 51mm x 12.5m	5
AFBT-4.0-200	4.0" x 41' / 102mm x 12.5m	5
600 AMP		
AFBT-2.5	2.5" x 41' / 64mm x 12.5m	5
AFBT-4.0	4.0" x 41' / 102mm x 12.5m	5



Aquasol® Water Soluble Tape

Aquasol® Water Soluble Tape is a pressure sensitive water soluble tape recommended to hold purge dams in position, and when needed to splice two or more pieces of Aquasol paper together. Sold in rolls.



Part No.	Type	Dimensions	Case Qty
ASWT-1	Roll	1" x 300' / 2.5cm x 92m	24
ASWT-2	Roll	2" x 300' / 5.0cm x 92m	12