

PRODUCT INFORMATION

Green PVC Work Shelter Cover

EZTENTTGCOV

SUMMARY

Our Green PVC Cover for Work Shelter Frames is recommended for applications where no external visibility is required. It's matt finish eliminates glare. Our Low Vis Green work shelter gives a high performance in all welding applications and is reinforced for extra strength and tear resistance.

TARGET APPLICATIONS

MIG, TIG, Stick and Gas welding applications.



FURTHER INFORMATION

Measuring 2mtr x 2mtr x 2mtr and suitable for MIG, TIG, Stick and Gas welding applications, our reinforced PVC green work shelters protect the weld and welder from the elements, and passers-by or colleagues from the welding arc and spatter.

Both this type and our durable white coated canvas cover are suitable for a number of other covered, non-welding related operations.

When supported by our strong, lightweight tubular steel frame (available separately), they are fast and east to erect and can be moved intact. The front can be left open or closed for partial or complete enclosure.

ARTICLES & ACCESSORIES

| Part Number | Product Description |
|-------------|--------------------------|
| EZTENTTGCOV | Green Work Shelter Cover |
| EZTENTWSFRM | Work Shelter Frame |

TECHNICAL SPECIFICATION

| Conformity | EN1598*:1998 |
|--------------------------------------|--|
| Flame Retardent | BS5438, test 2A and 2B |
| Material | Dark green, matt finish reinforced PVC |
| Cold crack | -6°C |
| Burst Strength | 825 MIN |
| Breaking Load (N/5cm) | L 340 MIN T 220 MIN |
| Tongue Tear | L 130 MIN T 220 MIN |
| Resistance to Flex Cracking (cycles) | 250,000 MIN |
| Storage conditions | -5°C to +25°C room temp |
| Cleaning | Wash in mild detergent |
| Weight | 340g/m² (±7.5%) |
| Thickness | 450 micron nominal |

For further information, contact Weldability | Sif technical support on 0870 330 7757 or email service@weldability-sif.com

Doc Ref: WELDABILITY/PSI/EZTENTTGCOV