



PRODUCT INFORMATION

LEAK-TEK/ LEAK TEK T LEAK DETECTOR

**EG3001
EG3002**

SUMMARY

The Leak-Tek /Leak Tek T Leak Detector is used to expose leaks and cracks in gas equipment.

TARGET APPLICATIONS

Leak-Tek/ Leak Tek T is suitable for use in processes that involve using gas, such as Oxy/Acetylene or Oxy/Propane equipment- hoses, regulator nuts, shank valves, headnuts etc as well as MIG and TIG regulators. Also ideal for use on installs to ensure all equipment is in perfect condition before use.



FURTHER INFORMATION

The Leak-Tek spray is an oil-free, non-toxic, milky spray, available in either a spray can or a trigger bottle. This product is non-flammable, non-corrosive, bio-degradable, environmentally friendly with no CFC's and will not form combustible mixtures with other gases.

In addition, the Leak Tek T trigger spray, is EN14291:2004 compliant and it's non-corrosive formula eliminates cylinder nozzle degradation.

To test, fill the pipes and spray the leak detector over the connections. If the spray bubbles, this indicates a leak in the equipment. When sprayed, it gives a low discharge milky liquid which all dried residue can be washed away by water.

This product is not suitable for use with phosphorous or phosphorous compound gases, or on medical gases where ingress into the gas may occur.

ARTICLES & ACCESSORIES

Part Number	Product Description
EG3001	LEAK-TEK SPRAY CAN
EG3002	LEAK-TEK T TRIGGER SPRAY

TECHNICAL SPECIFICATION

Compliant	Trigger Spray- EN14291:2004
Size	400ml aerosol spray/1ltr trigger bottle
Appearance	White milky liquid
Removal	Can be washed away with water

For further information, contact Weldability | Sif technical support on **0870 330 7757** or email service@weldability-sif.com