

# **ITW** Performance Polymers

## SAFETY DATA SHEET ALUMINIUM PUTTY (F) RESIN

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

|                |                           |
|----------------|---------------------------|
| Product name   | ALUMINIUM PUTTY (F) RESIN |
| Product number | X0002                     |
| UFI            | UFI: G110-X039-700P-RV3F  |

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

|                 |        |
|-----------------|--------|
| Identified uses | Resin. |
|-----------------|--------|

#### 1.3. Details of the supplier of the safety data sheet

|          |   |
|----------|---|
| Supplier | ITW Performance Polymers<br>Bay 150<br>Shannon Industrial Estate<br>Co. Clare<br>Ireland<br>V14 DF82<br>353(61)771500<br>353(61)471285<br>customerservice.shannon@itwpp.com |
|----------|---|

#### 1.4. Emergency telephone number

|                     |                          |
|---------------------|--------------------------|
| Emergency telephone | +44(0)1235 239 670 (24h) |
|---------------------|--------------------------|

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

|                       |  |
|-----------------------|--|
| Physical hazards      | Not Classified   |
| Health hazards        | Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 |
| Environmental hazards | Aquatic Chronic 2 - H411                                     |

**Human health** The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.

#### 2.2. Label elements

##### Hazard pictograms



**Signal word** Warning

**Hazard statements** H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

## ALUMINIUM PUTTY (F) RESIN

|   |   |
|---|---|
| <b>Precautionary statements</b>               | <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p>   |
| <b>Supplemental label information</b>         | EUH205 Contains epoxy constituents. May produce an allergic reaction.   |
| <b>Contains</b>                               | EPOXY RESIN (Number average MW <= 700 )   |
| <b>Supplementary precautionary statements</b> | <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P391 Collect spillage.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p> |

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

|   |  |
|---|--|
| <b>EPOXY RESIN (Number average MW &lt;= 700 )</b>   | <b>30-60%</b>                                    |
| CAS number: 25068-38-6  | EC number: 500-033-5                             |
|   | REACH registration number: 01-2119456619-26-0000 |
| <b>Classification</b><br>Skin Irrit. 2 - H315<br>Eye Irrit. 2 - H319<br>Skin Sens. 1 - H317<br>Aquatic Chronic 2 - H411 |  |

The full text for all hazard statements is displayed in Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

|                            |   |
|----------------------------|---|
| <b>General information</b> | Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).                             |
| <b>Inhalation</b>          | Move affected person to fresh air at once. Get medical attention if any discomfort continues.   |
| <b>Ingestion</b>           | Rinse mouth thoroughly with water. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. |
| <b>Skin contact</b>        | Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.                |
| <b>Eye contact</b>         | Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.             |

### 4.2. Most important symptoms and effects, both acute and delayed

## ALUMINIUM PUTTY (F) RESIN

**General information** The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** No specific recommendations. If in doubt, get medical attention promptly.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with foam, carbon dioxide or dry powder.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Irritating gases or vapours.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Control run-off water by containing and keeping it out of sewers and watercourses.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation.

### 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Use only in well-ventilated areas. Handle and open container with care. Keep away from heat, sparks and open flame. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

## ALUMINIUM PUTTY (F) RESIN

**Ingredient comments** No exposure limits known for ingredient(s).

### EPOXY RESIN (Number average MW <= 700 ) (CAS: 25068-38-6)

#### DNEL

Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day  
Workers - Inhalation; Short term systemic effects: 12.25 mg/m<sup>3</sup>

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

#### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

#### Hand protection

Wear protective gloves made of the following material: Rubber or plastic. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

#### Other skin and body protection

No specific recommendations.

#### Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace. Promptly remove any clothing that becomes wet or contaminated.

#### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                 |   |
|---------------------------------|---|
| Appearance                      | Paste.                                  |
| Colour                          | Grey.                                   |
| Odour                           | Slight.                                 |
| pH                              | pH (concentrated solution): 7.0 @ 20 °C |
| Melting point                   | n/d°C                                   |
| Initial boiling point and range | >260°C @                                |
| Flash point                     | > 204°C                                 |
| Vapour pressure                 | <0.03 mmHg @ °C                         |
| Relative density                | 2.80 @ 20 °C°C                          |

## ALUMINIUM PUTTY (F) RESIN

**Solubility(ies)** Slightly soluble in water.

**Auto-ignition temperature** >300°C

### 9.2. Other information

**Other information** Not available.

**Volatile organic compound** This product contains a maximum VOC content of 0 %.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Strong oxidising agents. Acids. Amines.

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not available.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid** Avoid contact with the following materials: Strong oxidising agents. Strong acids. Amines.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Vapours/gases/fumes of: Aldehydes.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Skin contact** Irritating to skin. May cause sensitisation by skin contact. The product contains a small amount of sensitising substance. May cause sensitisation or allergic reactions in sensitive individuals.

**Eye contact** Irritating to eyes.

**Acute and chronic health hazards** The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.

**Route of exposure** Inhalation Ingestion. Skin and/or eye contact

## SECTION 12: Ecological information

**Ecotoxicity** Avoid releasing into the environment. The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### 12.1. Toxicity

**Toxicity** Very toxic to aquatic organisms.

### 12.2. Persistence and degradability

**Persistence and degradability** There are no data on the degradability of this product.

## ALUMINIUM PUTTY (F) RESIN

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

### 12.4. Mobility in soil

**Mobility** Do not discharge into drains or watercourses or onto the ground.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** Not available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** When handling waste, the safety precautions applying to handling of the product should be considered.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Waste class** 08 04 99

## SECTION 14: Transport information

**General** No other information known.

### 14.1. UN number

**UN No. (ADR/RID)** 3082

**UN No. (IMDG)** 3082

**UN No. (ICAO)** 3082

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700 ))

**Proper shipping name (IMDG)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700 ))

**Proper shipping name (ICAO)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700 ))

**Proper shipping name (ADN)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700 ))

### 14.3. Transport hazard class(es)

**ADR/RID class** 9

**ADR/RID label** 9

**IMDG class** 9

**ICAO class/division** 9

## ALUMINIUM PUTTY (F) RESIN

### Transport labels



### 14.4. Packing group

|                       |     |
|-----------------------|-----|
| ADR/RID packing group | III |
| IMDG packing group    | III |
| ICAO packing group    | III |

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

|  |          |
|--|----------|
| EmS                                    | F-A, S-F |
| Emergency Action Code                  | •3Z      |
| Hazard Identification Number (ADR/RID) | 90       |
| Tunnel restriction code                | (E)      |

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

|                           |   |
|---------------------------|---|
| Revision date             | 17/02/2021  |
| Revision                  | 17  |
| Supersedes date           | 03/04/2018  |
| Hazard statements in full | H315 Causes skin irritation.<br>H317 May cause an allergic skin reaction.<br>H319 Causes serious eye irritation.<br>H411 Toxic to aquatic life with long lasting effects. |

## ALUMINIUM PUTTY (F) RESIN

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.