

Gas Regulators

Key Features

- 50mm gauges conforming to ISO 5171
- Forged brass body & bonnet
- Colour coded knobs for ease of use & clear identification of gas type
- 300 bar capacity
- Conform to ISO 2503



Single Stage Plugged

Oxygen: 300 Bar
Max Outlet Pressure: 10 Bar
Order Code: SSOXYP

Propane: 25 Bar
Max Outlet Pressure: 4 Bar
Order Code: SSPROPP

Acetylene: 25 Bar
Max Outlet Pressure: 1.5 Bar
Order Code: SSACETP



Single Stage 1 Gauge

Argon: 300 Bar
Max Outlet Pressure: 35 lpm flow
Order Code: SSARG1G

Argon
Pre-set 4 Bar
Order Code: SSARG1GPS



Single Stage 2 Gauge

Oxygen: 300 Bar
Max Outlet Pressure: 10 Bar
Order Code: SSOXY2G

Argon: 300 Bar
Max Outlet Pressure: 35 lpm flow
Order Code: SSARG2G

Acetylene: 25 Bar
Max Outlet Pressure: 1.5 Bar
Order Code: SSACET2G

Carbon Dioxide: 300 Bar
Max Outlet Pressure: 4 Bar
Order Code: SSCO22G

Two Stage 2 Gauge

Key Features

- These 2 stage regulators are designed for use where constant pressure and flows are critical
- 50mm gauges conforming to ISO 5171
- Colour coded knobs for ease of use & clear identification of gas type
- Forged brass body & bonnet
- 300 bar capacity
- Conform to ISO 2503



Oxygen: 300 Bar
Max Outlet Pressure: 10 Bar
Order Code: TSOXY2G



Acetylene: 25 Bar
Max Outlet Pressure: 1.5 Bar
Order Code: TSACET2G



Argon: 300 Bar
Max Outlet Pressure: 10 Bar
Order Code: TSARG2G