



### Technical Data

Input Voltage	AC 230V - 50/60 Hz
I <sub>eff</sub> (A)	15.5
Input Power (kVA)	6
Current Range (A)	10 - 140
Duty Cycle @ 40°C	140A @ 35%
No-Load Voltage (V)	63
Efficiency (%)	85
Power Factor	0.7
Protection/Insulation Class	IP21/F
Dimensions (LxWxH mm)	313 x 130 x 250
Weight (Kg)	4.7

### Key Features

- Professional quality IGBT Inverter
- Anti-Stick, Arc-Force Lift TIG
- Hot Start for those difficult to strike electrodes
- 40Khz inverter frequency, high efficiency
- Compact size, lightweight and modern design
- Heavy duty 16-25mm dinse sockets
- Easy arc starting, minimal spatter
- Auto-compensation for voltage fluctuation
- High quality tactile rubber finish to mouldings and handle
- Supplied in full colour packaging
- Can weld electrodes of up to 3.2mm
- Generator friendly\*\*



### Optional



JSB-01 Site Bag



JSS-01 Shoulder Strap



WCS25-3 MMA Leads

### Package Includes

Inverter power source, Cable plugs, Operating instructions, 5 year warranty\*



\* 5 year warranty subject to product registration \*\*Generators should have regulated output