

TC40

Portable pipe beveling machine

Range: 10 - 48.3mm o/d

Functions: external beveling
internal bevelling
facing
J prepping
compound angles

Materials: any kind of steel & exotic alloys

Power: pneumatic, electric

Pipe beveling machine with OD locking system from 0.39" to 1.9" available in pneumatic and electric version.

The machine is supplied with several locking jaws that are built according to the diameters to be worked.

The TC40 is suitable for working in tight clearances and in any occasion where locking in the ID is prohibited.



TC40

TECHNICAL FEATURES

		PNEUMATIC	ELETTRIC
OD Locking Range	mm (inches)	10 - 48.3 (0.39 - 1.9)	10 - 48.3 (0.39 - 1.9)
Idle Speed	(Rpm)	215	360
Stroke	mm (inches)	30 (1.18)	30 (1.18)
Max Chuck Torque	Nm	9 (6 bar) 27 (8 bar)	14
Electric motor power	Hp (W)	0.59 (435)	-
Air Consumption	NI/min (cfm)	615 (21.7)	-
Air pressure	Bar (psi)	6 ÷ 8 (87 ÷ 116)	-
Air Hose Connection	(inches)	1/2"	-
Electric Motor Power	W	-	720
Tension	Volt	-	110/230
Frequency	Hz	-	50/60
Max Acoustic Emission	Db	75	75
Machine Weight	Kg	10	10